



## PRISIONERO ALLEN ISO 12.9 UNC

Código	Diámetro	Largo "L" nom.	Envase	Medida Llave "B"	Penetración (*) mínima (mm)	Torque (Nm) Recomendado	Resistencia a la tracción (kN)
<b>Pavonado</b>							
01PAC	#8-32[5/32]	1/4	25 U	5/64	2,3	6,21	10,8
02PAC	#8-32[5/32]	5/16					
03PAC	#8-32[5/32]	3/8					
04PAC	#8-32[5/32]	1/2					
05PAC	#10-24[3/16]	1/4	25 U	3/32	2,5	8,92	13,5
06PAC	#10-24[3/16]	5/16					
07PAC	#10-24[3/16]	3/8					
09PAC	#10-24[3/16]	1/2					
10PAC	#10-24[3/16]	5/8					
11PAC	#10-24[3/16]	3/4					
12PAC	#10-24[3/16]	1"					
14PAC	1/4-20	1/4					
16PAC	1/4-20	5/16	20 U	1/8	3,2	22,6	24,6
18PAC	1/4-20	3/8					
20PAC	1/4-20	1/2					
21PAC	1/4-20	5/8					
22PAC	1/4-20	3/4					
24PAC	1/4-20	1"					
26PAC	5/16-18	3/8					
27PAC	5/16-18	1/2	10 U	5/32	4,0	46,9	40,5
29PAC	5/16-18	5/8					
33PAC	5/16-18	3/4					
35PAC	5/16-18	1"					
36PAC	5/16-18	1 1/4					

(\*) Penetración de llave en receso hexagonal.

