



HILO POR METRO UNC

Código	Diámetro	Largo, mt	Envase	Peso, kg cada barra	Diám Ext , mm Mín - Max	Resistencia Max , kg (*)	Códigos golilla/tuerca	Código taco de anclaje
03HPM	3/16-24	1,0	100 U	0.10	4.61 - 4.80	190	03GPC / 200TH1	
04HPM	1/4-20		100 U	0.17	6.11 - 6.32	350	01GPF / 201TH1	101TAN
05HPM	5/16-18		50 U	0.29	7.68 - 7.90	590	02GPF / 202TH1	106TAN
06HPM	3/8-16		25 U	0.40	9.25 - 9.49	880	03GPF / 203TH1	102TAN
07HPM	7/16-14		20 U	0.57	10.81 - 11.07	1210	04GPF / 204TH1	
08HPM	1/2-13		20 U	0.75	12.38 - 12.66	1620	05GPF / 206TH1	103TAN
09HPM	1/2-12		20 U	0.75	12.20 - 12.67	1550	05GPF / 205TH1	
10HPM	5/8-11		10 U	1.10	15.52 - 15.83	2590	07GPF / 208TH1	104TAN
11HPM	3/4-10		5 U	1.85	18.67 - 19.00	3850	08GPF / 209TH1	105TAN
12HPM	7/8-9		5 U	2.30	21.82 - 22.17	5330	09GPF / 210TH1	
13HPM	1"-8		5 U	3.10	24.96 - 25.34	7010	10GPF / 211TH1	
14HPM	1 1/4-7		5 U	5,26	31.27 - 31.69	11250	11GPF / 212TH1	
15HPM	1 1/2-6		5 U	7,14	37.57 - 38.03	16340	12GPF / 213TH1	

Envase Pequeño

04HPM	1/4-20	1,0	10 U	0.17	6.11 - 6.32	350	01GPF / 201TH1	101TAN
05HPM	5/16-18		10 U	0.29	7.68 - 7.90	590	02GPF / 202TH1	106TAN
06HPM	3/8-16		10 U	0.40	9.25 - 9.49	880	03GPF / 203TH1	102TAN
07HPM	7/16-14		10 U	0.57	10.81 - 11.07	1210	04GPF / 204TH1	
08HPM	1/2-13		10 U	0.75	12.38 - 12.66	1620	05GPF / 206TH1	103TAN
10HPM	5/8-11		5 U	1.10	15.52 - 15.83	2590	07GPF / 208TH1	104TAN
11HPM	3/4-10		5 U	1.85	18.67 - 19.00	3850	08GPF / 209TH1	105TAN
12HPM	7/8-9		5 U	2.30	21.82 - 22.17	5330	09GPF / 210TH1	

Zincado Brillante

B03HPM	3/16-24	1,0	100 U	0.10	4.61 - 4.80	190	03GPC / 200TH1	
B04HPM	1/4-20		100 U	0.17	6.11 - 6.32	350	01GPF / B201TH1	101TAN
B05HPM	5/16-18		50 U	0.29	7.68 - 7.90	590	02GPF / B202TH1	106TAN
B06HPM	3/8-16		25 U	0.40	9.25 - 9.49	880	03GPF / B203TH1	102TAN
B07HPM	7/16-14		20 U	0.57	10.81 - 11.07	1210	04GPF / B204TH1	
B08HPM	1/2-13		20 U	0.75	12.38 - 12.66	1620	05GPF / B206TH1	103TAN
B09HPM	1/2-12		20 U	0.75	12.20 - 12.67	1550	05GPF / B205TH1	
B10HPM	5/8-11		10 U	1.10	15.52 - 15.83	2590	07GPF / B208TH1	104TAN
B11HPM	3/4-10		10 U	1.85	18.67 - 19.00	3850	08GPF / B209TH1	105TAN
B12HPM	7/8-9		5 U	2.30	21.82 - 22.17	5330	09GPF / B210TH1	
B13HPM	1"-8		5 U	3.10	24.96 - 25.34	7010	10GPF / B211TH1	
B14HPM	1 1/4-7		5 U	5,26	31.27 - 31.69	11250	11GPF / B212TH1	
B15HPM	1 1/2-6		5 U	7,14	37.57 - 38.03	16340	12GPF / B213TH1	

Envase pequeño - Zincado Brillante

B04HPM	1/4-20	1,0	10 U	0.17	6.11 - 6.32	350	01GPF / B201TH1	101TAN
B05HPM	5/16-18		10 U	0.29	7.68 - 7.90	590	02GPF / B202TH1	106TAN
B06HPM	3/8-16		10 U	0.40	9.25 - 9.49	880	03GPF / B203TH1	102TAN
B08HPM	1/2-13		10 U	0.75	12.38 - 12.66	1620	05GPF / B206TH1	103TAN
B10HPM	5/8-11		5 U	1.10	15.52 - 15.83	2590	07GPF / B208TH1	104TAN
B11HPM	3/4-10		5 U	1.85	18.67 - 19.00	3850	08GPF / B209TH1	105TAN

Galvanizado en Caliente

G08HPM	1/2-13	1,0	20 U	0.75	12.38 - 12.66	1620	05GPF / 206TH1	103TAN
G10HPM	5/8-11		10 U	1.10	15.52 - 15.83	2590	07GPF / 208TH1	104TAN
G11HPM	3/4-10		5 U	1.85	18.67 - 19.00	3850	08GPF / 209TH1	105TAN
G12HPM	7/8-9		5 U	2.30	21.82 - 22.17	5330	09GPF / 210TH1	
G13HPM	1"-8		5 U	3.10	24.96 - 25.34	7010	10GPF / 211TH1	

Envase pequeño - Galvanizado en Caliente

G08HPM	1/2-13	1,0	1 U	0.75	12.38 - 12.66	1620	05GPF / 206TH1	103TAN
G10HPM	5/8-11		1 U	1.10	15.52 - 15.83	2590	07GPF / 208TH1	104TAN
G11HPM	3/4-10		1 U	1.85	18.67 - 19.00	3850	08GPF / 209TH1	105TAN

(*) Resistencia a la fluencia (cuando comienza a deformarse en forma permanente)

HILO POR 3 METROS UNC

Código	Diámetro	Largo, mt	Envase	Peso, kg cada barra	Diám Ext , mm Mín - Max	Resistencia Max , kg (*)	Códigos golilla / tuerca	Código taco de anclaje
--------	----------	-----------	--------	---------------------	-------------------------	--------------------------	--------------------------	------------------------

Bruto

04HM3	1/4-20	3,0	50 U	0,55	6.11 - 6.32	350	01GPF / 201TH1	101TAN
05HM3	5/16-18		25 U	0,91	7.68 - 7.90	590	02GPF / 202TH1	106TAN
06HM3	3/8-16		20 U	1,25	9.25 - 9.49	880	03GPF / 203TH1	102TAN
08HM3	1/2-13		10 U	2,40	12.38 - 12.66	1620	05GPF / 206TH1	103TAN
09HM3	1/2-12		10 U	2,40	12.20 - 12.67	1550	05GPF / 205TH1	
10HM3	5/8-11		10 U	3,70	15.52 - 15.83	2590	07GPF / 208TH1	104TAN
11HM3	3/4-10		5 U	5,50	18.67 - 19.00	3850	08GPF / 209TH1	105TAN
12HM3	7/8-9		5 U	7,60	21.82 - 22.17	5330	09GPF / 210TH1	
13HM3	1"-8		2 U	10,00	24.96 - 25.34	7010	10GPF / 211TH1	
14HM3	1 1/4-7		1 U	15,60	31.27 - 31.69	11250	11GPF / 212TH1	
15HM3	1 1/2-6		1 U	22,90	37.57 - 38.03	16340	12GPF / 213TH1	

Zincado Brillante

B04HM3	1/4-20	3,0	50 U	0,55	6.11 - 6.32	350	B01GPFU / B201TH1	101TAN
B05HM3	5/16-18		25 U	0,91	7.68 - 7.90	590	B02GPFU / B202TH1	106TAN
B06HM3	3/8-16		20 U	1,25	9.25 - 9.49	880	B03GPFU / B203TH1	102TAN
B08HM3	1/2-13		10 U	2,40	12.38 - 12.66	1620	B05GPFU / B206TH1	
B09HM3	1/2-12		10 U	2,40	12.20 - 12.67	1550	B05GPFU / B205TH1	
B10HM3	5/8-11		10 U	3,70	15.52 - 15.83	2590	B07GPFU / B208TH1	104TAN
B11HM3	3/4-10		5 U	5,50	18.67 - 19.00	3850	B08GPFU / B209TH1	105TAN
B12HM3	7/8-9		5 U	7,60	21.82 - 22.17	5330	B09GPFU / B210TH1	
B13HM3	1"-8		2 U	10,00	24.96 - 25.34	7010	10GPFU / B211TH1	
B14HM3	1 1/4-7		1 U	15,60	31.27 - 31.69	11250		
B15HM3	1 1/2-6		1 U	22,90	37.57 - 38.03	16340		

(*) Resistencia a la fluencia (cuando comienza a deformarse en forma permanente)

