



PERNO PARKER ROSCA UNF GRADO ISO 12.9

Código	Diámetro	Largo "L"	Envase		Diámetro Cabeza "A"	Altura Cabeza "H"	Medida Llave "B"	Torque (Nm) Recomendado	Resistencia a la tracción (kN)
Pavonado									
200PPK	#10-32	1/2	20	U	7.9	4.8	5/32	8.9	13.5
201PPK		5/8							
202PPK		3/4							
203PPK		1"							
204PPK		1 1/4							
205PPK		1 1/2							
207PPK	1/4-28	1/2	20	U	9.5	6.3	3/16	22.6	24.6
208PPK		3/4							
209PPK		1"							
210PPK		1 1/4							
211PPK		1 1/2							
213PPK	5/16-18	3/4	10	U	11.9	7.9	1/4	46.9	40.5
214PPK		1"							
215PPK		1 1/4							
216PPK		1 1/2							
217PPK		2"							
219PPK	3/8-16	3/4	5	U	14.2	9.5	5/16	83.6	53.9
220PPK		1"							
221PPK		1 1/4							
222PPK		1 1/2							
223PPK		2"							
224PPK		2 1/2							
226PPK	1/2-13	3/4	5	U	19.0	12.7	3/8	203.0	109.8
227PPK		1"							
228PPK		1 1/4							
229PPK		1 1/2							
231PPK		2"							
232PPK		2 1/2							

