



TARUGO NYLON PARA AMARRA

Código	Diám.	Largo "L"	Envase		Perforac. "D"	Profundidad Perforac. "A"	Ancho Máximo Amarra	Resistencia Rotura Oreja	Tornillo a utilizar	
01TRAC	M-5	25	100	U	5 mm	30 mm	3.6 mm	18.2 kg	#5 (3.0mm) - #6 (3.5mm)	
02TRAC	M-6	30	100	U	6 mm	35 mm	3.6 mm	18.2 kg	#6 (3.5mm) - #8 (4.2mm)	
03TRAC	M-8	40	50	U	8 mm	45 mm	4.8 mm	22.2 kg	#8 (4.2mm) - #10 (4.6mm)	
04TRAC	M-10	50	25	U	10 mm	55 mm	7.6 mm	54.5 kg	#10 (4.6mm) - #12 (5.4mm)	
01TRAC-F	M-5	25	70	U	10b/7u	5 mm	30 mm	3.6 mm	18.2 kg	#5 (3.0mm) - #6 (3.5mm)
02TRAC-F	M-6	30	150	U	30b/5u	6 mm	35 mm	3.6 mm	18.2 kg	#6 (3.5mm) - #8 (4.2mm)
03TRAC-F	M-8	40	150	U	30b/5u	8 mm	45 mm	4.8 mm	22.2 kg	#8 (4.2mm) - #10 (4.6mm)
04TRAC-F	M-10	50	90	U	30b/3u	10 mm	55 mm	7.6 mm	54.5 kg	#10 (4.6mm) - #12 (5.4mm)
01TRAC-G	M-5	25	100	U	5b/20u	5 mm	30 mm	3.6 mm	18.2 kg	#5 (3.0mm) - #6 (3.5mm)
02TRAC-G	M-6	30	150	U	10b/15u	6 mm	35 mm	3.6 mm	18.2 kg	#6 (3.5mm) - #8 (4.2mm)
03TRAC-G	M-8	40	150	U	10b/15u	8 mm	45 mm	4.8 mm	22.2 kg	#8 (4.2mm) - #10 (4.6mm)
04TRAC-G	M-10	50	60	U	10b/6u	10 mm	55 mm	7.6 mm	54.5 kg	#10 (4.6mm) - #12 (5.4mm)

AMARRA CABLE DE NYLON

Código	Ancho "A"	Largo "L"	Envase	
01AMA	3.6	140mm	50	U
02AMA	4.8	160mm	50	U